



HANNAY & ASSOCIATES, ARCHITECTS
 1726 South Hillside, Wichita, Kansas, 67211
 Phone: (316) 853-8955
 Fax: (316) 684-1441

2019 GENESIS HEALTH WESTROADS
 1212 NORTH 162ND STREET
 OMAHA, NE 68114



PLUMBING FIXTURE SCHEDULE						
MARK	IMAGE	DESCRIPTION	PIPING CONNECTIONS			
			COLD WATER	HOT WATER	WASTE	VENT
-		WATER HAMMER ARRESTERS - PROVIDE BELLOWES OR PISTON TYPE WATER HAMMER ARRESTERS AT EACH FIXTURE GROUP. SIZE AND INSTALL IN ACCORDANCE WITH MANUFACTURERS RECOMMENDATIONS AND POI STANDARD WH 201. INSTALL IN AN ACCESSIBLE LOCATION AND PROVIDE ACCESS DOOR IN CEILING AND/OR WALL WHERE REQUIRED FOR PROPER ACCESS. PRE-CHARGED, BELLOWES TYPE, ALL STAINLESS STEEL CONSTRUCTION, ASSE1010 APPROVED, POI CERTIFIED. PRE-CHARGED WITH 60 PSIG AIR, COPPER BODY, BRASS OR HIGH HEAT POLY-PROPYLENE PISTON WITH DUAL EDPM O-RING SEALS LUBRICATED WITH FDA APPROVED SILICONE LUBRICANT. POI CERTIFIED, ASSE 1010 APPROVED FOR SEALED WALL INSTALLATION.	POI# / SFU AA / 1-3 A / 1-11 B / 12-32 C / 33-60 D / 61-113 E / 114-154 F / 155-330	POI# / SFU AA / 1-3 A / 1-11 B / 12-32 C / 33-60 D / 61-113 E / 114-154 F / 155-330	-	-
CO-1		CAST IRON FLOOR CLEANOUT WITH ADJUSTABLE NICKEL BRONZE TOP, ZURN ZN-1400 C.I.	-	-	2"	-
EW-1		ADA, BI-LEVEL, STAINLESS STEEL, FILTERED, VANDAL RESISTANT BUBBLER, BOTTLE FILLER, IN WALL CARRIER, ELKAY LZSTLWSVRSK.	1/2"	-	1-1/4"	1-1/4"
FD-1		CAST IRON BODY, FLASHING COLLAR, ADJUSTABLE STRAINER HEAD, NICKEL BRONZE WITH 3/8" STRAINER, ZURN ZN15-6S WITH SURE SEAL SS3509 TRAP GUARD. PROVIDE SQUARE TOP STRAINER HEAD IN TILE FLOOR APPLICATIONS.	-	-	2"	1-1/2"
FS-1		CAST IRON FLANGED RECEPTOR, ACID RESISTANT COATING, 8-1/2" SQUARE TOP, NICKEL BRONZE 1/2" GRATE, ABS SEDIMENT BUCKET, JAY R. SMITH 3101. PROVIDE WITH TRAP.	-	-	REFER TO PLANS	REFER TO PLANS
L-1		ADA, UNDERMOUNT, 16"x16"x5-1/2", STAINLESS STEEL ROUND LAVATORY, WITH OVERFLOW, DEARBORN DEAR2701 1-1/4" P-TRAP, BRASSCRAFT CR1912C SUPPLIES, TRUBRO 102W WRAP KIT, SINK SHALL BE JUST UCIF-ADA-16 FAUCET: ADA, DECK MOUNTED, 1.5 GPM, TEMPERATURE LIMIT STOP, CHROME PLATED, CERAMIC CARTRIDGES, SINGLE LEVER, GROHE 32710-001	1/2"	1/2"	1-1/4"	1-1/4"
L-2		ADA, WALL MOUNT, ZURN Z-1231 CONCEALED ARM CARRIER, 4"C.C. DEARBORN 750 OFFSET GRID DRAIN, DEARBORN 507 1-1/4" P-TRAP, BRASSCRAFT CR 1912AC SUPPLIES, TRU-BRO 102W HOT/COLD WRAP, VITREOUS CHINA WHITE 20"x18-1/4" WITH 4" CENTERS, KOHLER CHESAPEAKE K1729 FAUCET: DECK MOUNTED, CHROME PLATED, SINGLE HANDLE, 0.5 GPM KOHLER 15593-F5	1/2"	1/2"	1-1/4"	1-1/4"
MS-1		BASIN: MODEL STONE, 24"x24"x10", STAINLESS STEEL DRAIN WITH COMBINATION DOME STRAINER AND LINT BUCKET, VINYL BUMPER GUARD ON EXPOSED SIDES, MOP HANGER, HOSE AND HOSE BRACKET, CAULK BETWEEN MOP BASIN AND WALL WITH SILICON BASED CAULK, DEEP SEAL TRAP, FIAT MSB-2424 OR APPROVED EQUAL. FAUCET: VACUUM BREAKER, ADJUSTABLE TOP BRACE, 3/4" HOSE THREAD, BUCKET HOOK INLETS ON 8" CENTER, CHROME PLATED, STERN WILLIAMS T-10-VB PROVIDE 3/8" HOSE WITH 3/4" CHROME COUPLINGS, STAINLESS STEEL WALL BRACKET, STAINLESS STEEL MOP HANGER, AND STAINLESS STEEL SPLASH PANEL, ON SURROUNDING WALLS, PROVIDE 1/2" REDUCED PRESSURE ZONE BACKFLOW PREVENTER ADJACENT TO MOP SINK FOR CHEMICAL DISPENSER CONNECTION.	3/4"	3/4"	3"	1-1/2"
S-1		DOUBLE COMPARTMENT, TOP MOUNT, 19"x33"x7-1/2", SELF RIMMING, STAINLESS STEEL SINK (2) HOLES ON 4" FAUCET HOLE CENTERS, WITH JUST BASKET STRAINER, DEARBORN 510 1-1/2" P-TRAP, BRASSCRAFT CR1920AC SUPPLIES, JUST DL-1933-A-GR FAUCET: DECK MOUNTED, DELTA 190 FAUCET, 9" HIGH SPOUT, SINGLE LEVER HANDLE, 2.2 GPM, DELTA 190-SS.	1/2"	1/2"	2"	1-1/2"
S-2		SINGLE COMPARTMENT, UNDERMOUNT, ADA, 18"x18"x5-1/2", SELF RIMMING, STAINLESS STEEL SINK, (2) HOLES ON 8" FAUCET HOLE CENTERS, WITH JUST BASKET STRAINER, DEARBORN 510 1-1/2" P-TRAP, BRASSCRAFT CR19C ANGLE STOPS, JUST USL-1815-A-GR S.S. FAUCET: DECK MOUNTED, DELTA 710WFHDF FAUCET AND STRAINER, 11" HIGH GOOSENECK SPOUT, SINGLE LEVER HANDLE, 2.2 GPM LAMINAR FLOW, ADJUSTABLE HANDLE LIMIT STOP, DELTA 190-SS.	1/2"	1/2"	2"	1-1/2"
S-3		3-COMPARTMENT, TOP MOUNT, 22"x49"x7-1/2", SELF RIMMING, STAINLESS STEEL SINK, (2) FAUCETS WITH 4" FAUCET HOLE CENTERS, WITH JUST BASKET STRAINERS WITH 1-1/2" OUTLETS, BRASSCRAFT CR1920AC SUPPLIES, JUST TLN-2249-A-GR. FAUCET: DECK MOUNTED 3-HOLES WITH SINGLE HANDLE PULL-OUT SPOUT, 8" HIGH SPOUT, SINGLE LEVER HANDLE, 1.8 GPM, INTEGRAL DOUBLE CHECK VALVES IN SPOUT, PROVIDE TWO (2) DELTA 470-WE-DST FAUCETS.	1/2"	1/2"	2"	1-1/2"
SD-1		SHOWER DRAIN, CAST IRON FLANGED RECEPTOR, ACID RESISTANT COATING, 9"x4"x4" DEEP, ANTI-SPLASH ALUMINUM DOME STRAINER, STAINLESS STEEL SEDIMENT BUCKET WITH STAINLESS STEEL MESH SCREEN OVER SEDIMENT BUCKET, EXTENDED WIDE ELASTOMERIC FLANGE, NICKEL BRONZE. PROVIDE WITH TRAP, MIFAB FS1530-184-1-69-83-Z.	-	-	4"	2"

PLUMBING FIXTURE SCHEDULE						
MARK	IMAGE	DESCRIPTION	PIPING CONNECTIONS			
			COLD WATER	HOT WATER	WASTE	VENT
SH-1		DELTA 1000 SHOWER VALVE WITH DELTA T-13220 SHOWER TRIM.	1/2"	1/2"	-	-
SH-2		ADA COMPLIANT, DELTA 1000 SHOWER VALVE WITH DELTA T-13220 SHOWER TRIM, DELTA T-13020 DIVERTER VALVE, ALSON 462 HAND SHOWER, ALSON 486DS HOSE, ALSON 4880 SUPPLY ELBOW, ALSON 4900 VACUUM BREAKER, PROFLO PFG818FS GRAB BAR, KOHLER K422 HAND SHOWER HOLDER.	1/2"	1/2"	-	-
TD-1		TRENCH DRAIN - 16 GAUGE TYPE 304 STAINLESS STEEL CHANNEL AND REMOVEABLE GRATE, 80" LONG X 2-7/8" WIDE, PRE-PITCHED WITH CENTER OUTLET AND STAINLESS STEEL THREADED NIPPLE INCLUDE 2" CLAMP DOWN DRAIN BODY FOR WATERPROOF MEMBRANE.	-	-	2"	1-1/2"
DT-1		ADA, VITREOUS CHINA, ELONGATED BOWL, WHITE FLOOR MOUNTED, KOHLER K-4960-ET WITH ZURN 1221 HANGER PLATE. FLUSH VALVE: ADA, CHROME PLATED, SENSOR ACTIVATED, 0.5 GPF, BATTERY POWERED, DIAPHRAGM TYPE, SLOAN GZ OPTIMA PLUS 186-1.0 ES-S.	-	-	2"	1-1/2"
WC-1		ADA, VITREOUS CHINA, ELONGATED BOWL, WHITE FLOOR MOUNTED WATER CLOSET, 16-1/2" HIGH, KOHLER K-4302, 1-1/2" TOP SPUD, WHITE ELONGATED OPEN FRONT SEAT LESS COVER, CHURCH 295C. FLUSH VALVE: ADA, CHROME PLATED, SENSOR ACTIVATED, BATTERY POWERED, DIAPHRAGM TYPE, 1.5 GPF, ZURN WS1.	1"	-	4"	2"
WC-2		VITREOUS CHINA, SIPHON JET, ELONGATED BOWL, WHITE FLOOR MOUNTED WATER CLOSET, 15" HIGH, KOHLER K-4350, 1-1/2" TOP SPUD, WHITE ELONGATED OPEN FRONT SEAT LESS COVER, CHURCH 295C. FLUSH VALVE: CHROME PLATED, SENSOR ACTIVATED, BATTERY POWERED, DIAPHRAGM TYPE, 1.5 GPF, ZURN WS1.	1"	-	4"	2"

REMARKS:

- REFER TO ARCHITECTURAL PLANS AND ELEVATIONS FOR ADDITIONAL REQUIREMENTS, ROUGH IN DIMENSIONS, AND COORDINATION OF ACCESSORIES. FIXTURE MOUNTING LOCATIONS AND OPERATION OF FIXTURE SHALL NOT INTERFERE WITH ADJACENT ACCESSORIES OR THEIR OPERATION.
- CONTRACTOR SHALL COORDINATE ALL FIXTURES WITH OTHER TRADES. ANY CONFLICTS OR ADJUSTMENTS SHALL BE BROUGHT TO THE IMMEDIATE ATTENTION OF THE ENGINEER.
- COORDINATE SINK BASINS AND DRAIN OUTLETS WITH CASEWORK AND KNEE GUARDS. PROVIDE OFFSET TAILPIECES AS REQUIRED TO ACCOMMODATE INSTALLATION AND COMPLY WITH ADA REQUIREMENTS.
- COORDINATE FLUSH VALVE INSTALLATION WITH GRAB BARS IN ALL LOCATIONS.
- COORDINATE MOUNTING OF FAUCET SPOUTS WITH BASINS. FAUCET SHALL NOT DISCHARGE DIRECTLY INTO BASIN DRAIN AND SHALL PROVIDE SUFFICIENT CLEARANCE BETWEEN STREAM AND BASIN TO ALLOW FOR UNOBSTRUCTED HAND WASHING WITHOUT CONTACT WITH THE BASIN. CONTRACTOR SHALL OBTAIN AND COORDINATE WITH SHOP DRAWINGS FROM COUNTER AND CASEWORK MANUFACTURERS.
- COORDINATE DRAIN GRATE WITH FLOOR SLOPING AND FLOORING PATTERN FOR ALL FLOOR DRAINS, FLOOR SINKS, AND TRENCH DRAINS. DRAIN SHALL BE SET SUCH THAT DRAIN GRATE IS FLUSH WITH FINISHED FLOOR SURFACE AND COORDINATED WITH PATTERN. REFER TO ARCHITECTURAL PLANS AND DETAILS FOR ADDITIONAL INFORMATION.

DRAWINGS ISSUED		
NO.	DATE	ITEM ISSUED
2	10/04/19	ADDENDUM #2

COMPUTER DRAWING

DATE: APRIL 2019
 DRAWN BY: JSH
 CHECKED BY: EGS

SHEET

M6.1

OF SHEETS

2019 © COPYRIGHT
 PERMISSION TO REPRODUCE ANY PART OF THIS DOCUMENT IS HEREBY GRANTED SOLELY FOR THE PURPOSE OF THE CONSTRUCTION OF THE PROJECT OR THE ARCHIVING OF THIS PROJECT. UNAUTHORIZED USE OF THIS DOCUMENT WITHOUT THE WRITTEN PERMISSION OF SPECIALIZED ENGINEERING SOLUTIONS IS PROHIBITED BY COPYRIGHT LAW.
 DO NOT SCALE DRAWING. ALL DIMENSIONS AND CLEARANCES SHALL BE VERIFIED FROM APPROPRIATE SOURCES. ALL WORK SHALL BE COORDINATED PRIOR TO INSTALLATION. SEE SPECIFICATIONS.

SPECIALIZED ENGINEERING SOLUTIONS
 10360 Ellison Circle
 Omaha, NE 68134
 Phone: 402.991.5520
 www.specializedeng.com

SES PROJECT # 18435